ATOSA USA, INC.
Toll Free: 855-855-0399 Email: info@atosausa.com
www.atosa.com | www.atosausa.com
California, Colorado, Florida, Georgia, Illinois,
New Jersey, Ohio, Texas, Washington

"WE MAKE THE KITCHEN BETTER!"

Top Mount Reach-In Refrigerators

MODELS:

MBF15RSGR / MBF15RSGRL / MBF8004GR
MBF8004GRL / MBF8005GR / MBF8006GR

MBF15RSGR MBF15RSGRL MBF8004GR

Standard Features

- Top mount compressor with environmentally friendly R290 refrigerant
- Stainless steel exterior & interior
- Electronic temperature controller
- Maintains temperatures between 35°F – 38°F
- LED interior light(s)
- Recessed door handle(s)
- Door lock(s) standard
- Magnetic door gasket(s) standard for positive door seal
- Pre-installed casters
- Three (3) pre-installed shelves per section
- Down duct refrigeration to ensure even distribution of air
- Wall bracket standard for MBF15RSGR(L) and is required for use

MBF8004GRL MBF8005GR

Optional Accessories

- Extra shelves – includes 4 shelf clips per shelf
  MBF15RSGR(L) shelf part #: R060040000003
  MBF8004GR(L) shelf part #: W0402389
  MBF8005GR shelf part #: W0402385
  MBF8006GR shelf part #: W0402385 left/right shelf, part #: W0402386 middle shelf

MBF8006GR

For the best results of food preservation we recommend setting your refrigerator between 35°F to 38 °F

1. Don't forget to leave the unit some room to breathe!
2. Please clean the condenser frequently to give the unit more fresh air.

3 YEAR PARTS AND LABOR WARRANTY
5 YEAR COMPRESSOR PART WARRANTY

MBF8004GR(L)
MBF8005GR
MBF8006GR

REV. 07/26

ATOSA USA, INC.
Toll Free: 855-855-0399 Email: info@atosausa.com
www.atosa.com | www.atosausa.com
California, Colorado, Florida, Georgia, Illinois,
New Jersey, Ohio, Texas, Washington

"WE MAKE THE KITCHEN BETTER!"

SPECIFICATIONS

Models	Door	Capacity (Cu.Ft.)	Shelves	Casters (inch)	Rated Current (A)	Voltage (V/Hz/Ph)	HP	Refrigerant	Exterior Dimensions (inch)	Net Weight (lb)	Gross Weight (lb)
MBF15RSGR	1	13	3	4	2.1	115/60/1	1/7	R290	$17^{3/4}\times37\times81^{1/2}$	192	270
MBF15RSGRL	1	13	3	4	2.1	115/60/1	1/7	R290	$17^{3/4}\times37\times81^{1/2}$	192	270
MBF8004GR	1	21.4	3	4	2.1	115/60/1	1/7	R290	$28^{3/4}\times31^{3/4}\times81^{3/8}$	220	254
MBF8004GRL	1	21.4	3	4	2.1	115/60/1	1/7	R290	$28^{3/4}\times31^{3/4}\times81^{3/8}$	220	254
MBF8005GR	2	43.2	6	4	3.2	115/60/1	1/5	R290	$51^{3/4}\times31^{3/4}\times81^{3/8}$	340	390
MBF8006GR	3	64.9	9	4	4.2	115/60/1	1/4	R290	$77^{3/4}\times31^{3/4}\times81^{3/8}$	472	551

PLAN VIEW

MBF8004GR **MBF8004GRL** **MBF8005GR** **MBF8006GR**



SELF-CLOSING AND STAY OPEN DOOR FEATURE

MBF15RSGR **MBF15RSGRL**



Casters | Epoxy shelves | Door lock | Down duct | Temperature control

NEMA 5-15P

NEMA 15A/125V

Atosa is continuously improving products. Specifications are subject to change without notice.